



**OPERATION & MAINTENANCE**

Towels are fed by lever action until supply is depleted. Towel feed length is adjustable for economy by pin (supplied) limiting of lever stroke length. Unit may be reloaded with a full roll to automatically start when finished with an existing partial roll. Waste container is emptied manually on cycle determined by maintenance needs. Locking compartment and receptacle retainer prevents unauthorized access and removal.

**TECHNICAL INFORMATION / PRODUCT PROPERTIES**

Property	Value
Dimensions	17-1/4" [438] W x 56" [1422] H x 11-3/4" [299] D
Construction	Type 304 Stainless Steel - Satin Finish
Mounting	Semi-Recessed - w/6" collar
Capacity	Roll Towels - up to 800 ft. Length / 18.0 Gal. (68.0 L) Waste Capacity

**INSTALLATION**

Install unit in wall recess using four (4) #10 self-threading screws (by others) through concealed mounting holes provided. Note that top of Rough Wall Opening (RWO) is 3/4" [19] below top of unit. Suggested mounting height is 55" [1397] Above Finished Floor (AFF) to lever handle. For reduced height compliance with 6" [152] curb and compliance with 2010 ADA Accessibility Standards see Model #0463 or #046921 series.

Rough Wall Opening (RWO) required is 15-3/4 [400] W x 54-1/2" [1384] H x 4" [102] D minimum

**WARRANTY**

One (1) Year from date of Invoice